

## TECHNICAL DATASHEET

### 20535 // SAFE

|                 |                     |
|-----------------|---------------------|
| Material:       | Split leather, grey |
| Coating:        | -                   |
| Size(s):        | 9-11                |
| Packaging unit: | 60 pairs            |
| Certification:  | EN 388, EN 12477    |



AVAILABLE IN SIZES 9-11



SL



### Description

NITRAS SAFE, welding gloves (american safety welding gloves), split leather, grey (colour code: 1200), length 35 cm, fully lined, protection against contact heat (100° C, 15 seconds)

|                        | Material      | Colour |
|------------------------|---------------|--------|
| Palm                   | Split leather | Grey   |
| Index finger and thumb | Split leather | Grey   |
| Back of the hand       | Split leather | Grey   |
| Fingertips             | Split leather | Grey   |
| Cuff / knitted wrist   | Split leather | Grey   |

| EN 420:2003 + A1:2009  |  | Test parameter | Performance level | Test result |
|--|--|----------------|-------------------|-------------|
|  |  | Dexterity      | 1-5               | 5           |
| EN 388:2016  |  | Test parameter | Performance level | Test result |
| <br><b>3143X</b>    | Abrasion resistance                            |                | 1-4               | 3           |
|  | Blade cut resistance (Coupe-Test)              |                | 1-5               | 1           |
|  | Tear resistance                                |                | 1-4               | 4           |
|  | Puncture resistance                            |                | 1-4               | 3           |
|  | Blade cut resistance (TDM)                     |                | A-F               | X           |
| EN 12477:2001+A1:2005  |  | Test parameter | Performance level | Test result |
| <br><b>413X4X A</b> | Resistance to flammability                     |                | 1-4               | 4           |
|  | Contact heat resistance                        |                | 1-4               | 1           |
|  | Convective heat resistance                     |                | 1-4               | 3           |
|  | Radiant heat resistance                        |                | 1-4               | X           |
|  | Resistance to small splashes of molten metal   |                | 1-4               | 4           |
|  | Resistance to large quantities of molten metal |                | 1-4               | X           |