

ULTRANE 500





EN407

X1XXXX

ISO 13997:

5 N

ISO 18889

DEXTERITY

EN 420:

5/5

EN388



4121A

CAT.3

0075



Grip and skin protection for oily environments.

SPECIFIC ADVANTAGES

Durability

- Color adapted to dirty environements for a prolonged durability.
- Excellent abrasion resistance due to the nitrile coating

Productivity

• Grip and Proof coating ensures an excellent grip in oily environment. It also reduces muscle strain and boost productivity

Skin protection

- Oilproof, it repels oil penetration and reduce dermatitis
- Free of harmful substances: DMF Free

Guaranteed quality

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Washability

• Washable 3 times at 40° without any alteration on performances* to extend lifespan, reduce costs and waste

Additionnal benefits

Available in vending machine packaging

INDUSTRIES

- Automotive/mechanical industrv
- Mechanical industry
- Other industries
- Glass industry
- Agriculture sector

APPLICATIONS

- Maintenance in wet environments
- Handling glass sheets
- Re-entry tasks
- Cutting and stamping metal
- Maintenance in wet environments (water, oil, greases, hydrocarbons)
- Handling and sorting small, sharp parts
- Handling oily mechanical parts
- Handling sheet metal
- Machining parts using cutting oil

Edit 16/03/2022

MAPA SAS capital de 35.000.010 € 420, rue d'Estienne d'Orves 92705 Colombes Cedex France RCS Nanterre 314 307 720





ULTRANE 500

EN388	MECHANICAL HAZARDS
Ŀ	PERFORMANCE LEVELS (X = NOT TESTED)
<u>4</u> <u>1</u> <u>2</u> 0-4 0-5 0-4	1 A 0-4 A-F P Impact protection (optional) Cut resistance according to ISO
	13997 Puncture resistance ear resistance ut resistance
EN407	THERMAL RISKS (HEAT AND FIRE) PERFORMANCE LEVELS (X = NOT TESTED)
$\begin{array}{c c} \mathbf{X} & 1 & \mathbf{X} \\ \hline 0-4 & 0-4 & 0-4 \\ \hline \\ \end{array}$	X X X 0-4 0-4 Resistance to large quantities of molten metal
	Small splashes of molten metal Radiant heat resistant onvective heat resistance : heat resistance spread
GR	PROTECTION FROM PESTICIDES GR: Re-entry tasks

(PRODUCT DETAILS)

Interior finish	Seamless textile support
Gauge	13
Exterior finish	Ventilated back
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Knitted Cuff
Colour.s	Black
Size	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	1.1Ε+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	4.4E+11 Ω

LOGISTIC DETAILS

1 pair/bag 12 pairs/bag
96 pairs/carton

LEGISLATION

- $\,$ This product is not classified hazardous according to the regulation (EC) $\,$ n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/09/18/1953
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0075 | CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE

Edit 16/03/2022

ISO 18889

MAPA SAS capital de 35.000.010 € 420, rue d'Estienne d'Orves 92705 Colombes Cedex France RCS Nanterre 314 307 720 * Tests carried out on unworn gloves (i.e. in new condition) which differs from the reality in the field.

